

**RICE LAKE**  
WEIGHING SYSTEMS

# RoughDeck® QC Quick Clean

STAINLESS STEEL  
FLOOR SCALE



**磅** 三興製磅廠有限公司  
Sam Hing Scales Fty. Ltd.

Tel: (852) 2393 3148

Website: [www.samhing.com.hk](http://www.samhing.com.hk)

[www.samhing.com.hk](http://www.samhing.com.hk)

# RoughDeck® QC Quick Clean

## STAINLESS STEEL FLOOR SCALE



The rugged design incorporates 304 stainless steel construction and four welded seal load cells with PTFE cable designed for high temperatures and washdown areas.



Dual corner locks secure the deck to the base for safety, durability, and convenience.

Unique dual gas-shock design provides easy opening and gentle closing.



### Standard Features:

- Rugged washdown design
- Smooth, 304 stainless steel top deck
- Four stainless steel welded seal shear beam load cells
- Rigid 304 stainless steel tube frame
- Remote Tuffseal® stainless steel NEMA 4X junction box
- Four adjustable stainless steel SUREFOOT support feet
- 20 ft of SURVIVOR® hostile environment load cell cable to connect an indicator to the junction box
- Safety bar

### Options/Accessories:

- Stainless steel deck with treadplate
- Floor stand for indicator. Stainless steel, 36.3" high, and fits IQ plus® 355, IQ plus® 390-DC, IQ plus® 510, IQ plus® 590-DC and IQ plus® 710

If you require any further information, please feel free to contact our team.

Email: [sales@samhing.com.hk](mailto:sales@samhing.com.hk)



磅

三興製磅廠有限公司  
Sam Hing Scales Fty. Ltd.

Tel: (852) 2393 3148

Website: [www.samhing.com.hk](http://www.samhing.com.hk)

### Specifications:

End Load Capacity: 100% full scale

mV/V Output: 1.50-1.87 mV/V nominal

Remote J-Box: Stainless steel NEMA 4X enclosure can be located up to 10 ft away from the scale

Warranty: 5-year limited warranty



CC# 92-001A5

$n_{max} = 5,000$   
Class III

Shown with optional treadplate stainless steel deck.



### Dimensions/Capacities:

SIZE	CAPACITY LB (KG)	SHIP WT LB
2.5' x 2.5'	2000 lb (1000 kg)	158 lb
3' x 3'	2000 lb (1000 kg)	208 lb
4' x 4'	2000 lb (1000 kg)	338 lb
4' x 4'	5000 lb (2500 kg)	338 lb
4' x 4'	10,000 lb (5000 kg)	447 lb
4' x 5'	2000 lb (1000 kg)	406 lb
4' x 5'	5000 lb (2500 kg)	406 lb
4' x 5'	10,000 lb (5000 kg)	540 lb
4' x 6'	2000 lb (1000 kg)	477 lb
4' x 6'	5000 lb (2500 kg)	477 lb
4' x 6'	10,000 lb (5000 kg)	637 lb
5' x 5'	2000 lb (1000 kg)	478 lb
5' x 5'	5000 lb (2500 kg)	478 lb
5' x 5'	10,000 lb (5000 kg)	637 lb
5' x 7'	2000 lb (1000 kg)	705 lb
5' x 7'	5000 lb (2500 kg)	705 lb
5' x 7'	10,000 lb (5000 kg)	908 lb

Each scale is corner calibrated at the factory. Distributors must calibrate scale and indicator together.



Choose from a versatile line of digital weight indicators.